



ASTEC® TRANSPORT DOLLIES

ASTEC Transport Dollies are a solution that provides controlled movement of the ASTEC equipment to a desired location within a customer's facility. If overhead clearance, permanent plant structures or limited overhead crane travel is a challenge, the ASTEC Transport Dollies are a perfect solution.

Features and Benefits:

- > Low clearance of 30mm (floor to bottom of dolly).
- Swivel Casters with Stop Top Brake on Front Dolly, allow controlled movement and secure placement.
- Front Spring Caster prevents bottoming out on uneven floors.
- > Tow Motor and Industrial Fork Lift capable.
- > Steel Structure, providing durability of up to a combined weight of 26,000 lbs/13 tons.
- Highly compressed nylon casters, preserving floor surface and tread surface abrasion.





Front and Rear Transport Dollies

Micro-Poise Measurement Systems, LLC is constantly striving to provide complete system solutions to our customers, fulfilling their needs and requirements.

Micro-Poise Measurement Systems, LLC

For more than 90 years, Micro-Poise has been supplying innovative solutions that put us on the leading edge of final finish tire testing technology. Contact us today to see why The World is Turning to Micro-Poise for all of their final finish tire testing needs.





Front and Rear Transport Dollies



Front and Rear Transport Dolly in use with ASTEC Frame.

	Front Transport Dolly	Rear Transport Dolly
Load Capacity	13,200 lbs	13,200 lbs
Dimensions	2075mm W x1443mm L	2111mm W x 513mm L
(width x length)	(82 inch W x 57 inch L)	(83 inch W x 20 inch L)
Clearance	275mm/11 inches	275mm/11 inches
Roller Dimension	152mm (dia.)x 80mm (width)	152mm (dia.)x 80mm (width)
Part Number (sold as set)	14-00206 (set)	

Email us today: micropoise.csdsales@ametek.com

www.micropoise.com

MP USA

Tel: + 1-330-541-9100 Fax: +1-330-541-9111

MP Europe

Tel: +49-451-89096-0 Fax: +49-451-89096-24 **MP Korea**

Tel: +82-Fax: +82**MP China**

Tel: +86-20-8384-0122 Fax: +86-20-8384-0123